

SPECIFICATION OF DDW240/70L

Dimensions/ Weight

Length/Width/Height	17500*2650*3500 mm
Entry angle	13°
Machine weight	39 ton

Operator room

Length/Width/Height	6000*2500*2200 mm @ 2.0 ton
Environment control	Full closed, climate control with A/C
Control system	Electronic self-diagnostic PLC
Visualization	10" inch colour screen monitor * 3
Operation controls	Joysticks and levers

Engine

Make	Cummins
Rated power	410 KW
Rated speed	1900 rpm
Fuel tank capacity	500 L

Hydraulic system

Max pressure (rotary & carriage)	40 Mpa
Max pressure (control sys.)	35 Mpa
Hydraulic tank capacity	600 L

Under carriage

Structure	Box welded frame, self-propelled on track crawler
Travel speed	0-1.8 km/h, forward & reverse
Track	Steel type with rubber pad
Track plate width	500 mm

Drill mast

Transmission type	Rack & pinion
Rod support	Yes
Hose carrier	Full length of chain type
Setup mode	Cylinder type

Rotary drive

Rotary torque	70000/49000/27000 N.M
Rotary speed	40/57/105 r/min
Transmission	Gear box

Carriage

Maximum thrust/pullback force	2400 KN
Max travel speed	31 m/min
Max travel distance	9.5 m

Stake down

Anchoring type	Manual anchoring
Hole nos	4

Wrench assembly

Type	Clamp jaw
Max breakout torque	180000 Nm
Thread greasing	Automatic

Pipe loader

Type	One rod type pipe loader
------	--------------------------

Crane

Lifting capacity	3.2 ton
Control	Out doors

Drill pipe

Type	Φ 127*9600 mm
Thread	NC50

Tools

Back reamer	500, 600, 700, 800, 900, 1000, 1100, 1200 mm
-------------	--

※ Specifications for reference only subject to change prior to notice. ※

VARIETY OF USEFUL DOWN HOLE EQUIPMENT SUPPLIES



Special make drill pipe

Mud mixing & recycling

Cutting type Backreamer

Cone type Backreamer

Beacon housing & drill bit

F5 & Transmitter

Paratrack 2

DW/TXS CONSTRUCTION EQUIPMENT (BEI JING) CO., LTD.

No.6, Huoxing Fifth Street, Huo County Development Area Tongzhou District, Beijing, China.

Postal code: 101109 Tel: +86 10 80582365 Fax: +86 10 80582515 Web: www.dwtxs.cn Email: feishubing@dwtxs.com



DDW240/70L

HORIZONTAL DIRECTIONAL DRILL

DW/TXS CONSTRUCTION EQUIPMENT (BEI JING) CO.,LTD.

DWTXS

MASTER OF DRILL RIGS!



**PULL FORCE: 240 TON
TORQUE: 70000 NM**

DDW240/70L

MACHINE MAKE YOU FEEL CONFIDENT!



Broad anchoring board and rear supporting beam connected by the wire rope to give a stable anchoring during the maximum force pulling.

Movable clamping, level adjusting pipe loader, onboard lifting crane, all these equipment make sure the rig can give a safe and efficient pipe handling work on the rig.

Dual rod supporter on the anti-mud slippery beam let the rod even and stable before threaded into the shaft.

DWTKS

Steel track chassis equipped with individual engine for rig movement so the machine can be transit by itself and no need other traction for the short distance running.



Double cylinder jacking with sliding rack and mast to setting the optimal angle for a stable and efficient drilling.





WELL PREPARED MEANS
HIGH PERFORMANCE!

INSTALLATION OF PRODUCT PIPE!



Double cylinder jacking with sliding rack and mast to setting the optimal angle for a stable and efficient drilling.

HIGH PERFORMANCE!